



## PI5A4599A

### SOT<sub>INY</sub>™ Low Resistance, Low-Voltage Single-Supply SPDT Switch

#### Features

- Low On-Resistance: 10 ohms max.
- $R_{ON}$  Matching: 2 ohms max.
- $R_{ON}$  Flatness: 3.5 ohms max.
- Low 0.5nA Input Leakage at 25 °C
- 2V to 6V Single-Supply Operation
- Fast Switching Time
  - 15ns  $t_{ON}$
  - 7ns  $t_{OFF}$
- Break-Before-Make Switching Guaranteed
- 5pC max Charge Injection
- 225MHz Channel Bandwidth
- 76dB Off-Isolation at 1MHz
- TTL/CMOS Logic Compatible
- Low Power Consumption: 5 $\mu$ W
- Improved Direct Replacement for MAX4599
- Packages available:
  - 6-pin Small Compact SC70

#### Applications

- Communication Circuits
- Cellular Phones
- Audio and Video Signal Routing
- Portable Battery-Operated Equipment
- Data Acquisition Systems
- Computer Peripherals
- Telecommunications
- Relay Replacement
- Wireless Terminals and Peripherals


#### Description

The PI5A4599A is an improved, direct replacement for the MAX4599 single-pole, double-throw (SPDT) analog switch. Improved specifications include a low maximum ON resistance of 10 ohms and fast switching times ( $t_{ON}$  = 15ns max.,  $t_{OFF}$  = 7ns max.) with 5V supply operation. With a 2.5V supply, resistance is a low 40 ohms max.

Specifications are given for 2.5V, 3.3V and 5V power supply operation. Operating voltage range is 2.0V to 6.0V.

To minimize PC board area use, the PI5A4599A is available in a compact 6-pin SC70 package. Operating temperature range is –40°C to 85°C.

#### Functional Diagram, Pin Configuration



#### Truth Tables

| Logic | PI5A4599A |     |
|-------|-----------|-----|
|       | NC        | NO  |
| 0     | ON        | OFF |
| 1     | OFF       | ON  |



### Absolute Maximum Ratings

Voltages Referenced to GND

V+ ..... -0.5V to +7V

V<sub>IN</sub>, V<sub>COM</sub>, V<sub>NC</sub>, V<sub>NO</sub> (Note 1) ..... -0.5V to V<sub>CC</sub>+2V  
or 30mA, whichever occurs first

Current (any terminal) ..... ±30mA

Peak Current, COM, NO, NC

(Pulsed at 1ms, 10% duty cycle) ..... ±30mA

### Thermal Information

Continuous Power Dissipation

SC70-6 (derate 3.1mW/°C above +70°C) ..... 245mW

Storage Temperature ..... -65°C to +150°C

Lead Temperature (soldering, 10s) ..... +300°C

#### Note:

1. Signals on NC, NO, COM, or IN exceeding V+ or Gnd are clamped by internal diodes. Limit forward diode current to 30mA.

**Caution:** Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied.

### Electrical Specifications - Single +5V Supply

(V+ = +5V ± 10%, GND = 0V, V<sub>INH</sub> = 2.4V, V<sub>INL</sub> = 0.8V)

| Parameter  | Symbol  | Conditions   | Temp.(°C) | Min. <sup>(1)</sup> | Typ. <sup>(2)</sup> | Max. <sup>(1)</sup> | Units |
|--|---|--|-----------|---------------------|---------------------|---------------------|-------|
| <b>Analog Switch</b>                                   |   |  |           |                     |                     |                     |       |
| Analog Signal Range <sup>(3)</sup>                     | V <sub>ANALOG</sub>                             |  | Full      | 0                   |                     | V+                  | V     |
| On Resistance  | R <sub>ON</sub>                                 | V+ = 4.5V, I <sub>COM</sub> = -30mA,<br>V <sub>NO</sub> or V <sub>NC</sub> = +2.5V         | 25        |                     | 7                   | 8                   | ohm   |
|  |   |  | Full      |                     |                     | 10                  |       |
| On-Resistance Match<br>Between Channels <sup>(4)</sup> | ΔR <sub>ON</sub>                                |  | 25        |                     | 0.1                 | 0.5                 |       |
|  |   |  | Full      |                     |                     | 1                   |       |
| On-Resistance<br>Flatness <sup>(5)</sup>               | R <sub>FLAT(ON)</sub>                           | V+ = 5V,<br>I <sub>COM</sub> = -30mA,<br>V <sub>NO</sub> or V <sub>NC</sub> = 1V, 2.5V, 4V | 25        |                     | 2.72                | 3.5                 |       |
|  |   |  | Full      |                     |                     | 4                   |       |
| NO or NC Off<br>Leakage Current <sup>(6)</sup>         | I <sub>NO(OFF)</sub> or<br>I <sub>NC(OFF)</sub> | V+ = 5.5V, V <sub>COM</sub> = 0V,<br>V <sub>NO</sub> or V <sub>NC</sub> = 4.5V             | 25        | -0.5                | 0.18                | 0.5                 | nA    |
|  |   |  | Full      | -5                  |                     | 5                   |       |
| COM Off Leakage<br>Current <sup>(6)</sup>              | I <sub>COM(OFF)</sub>                           | V+ = 5.5V,<br>V <sub>COM</sub> = + 4.5V, V <sub>NO</sub> or<br>V <sub>NC</sub> = ± 0V      | 25        | -1.0                | 0.20                | 1.0                 |       |
|  |   |  | Full      | -10                 |                     | 10                  |       |
| COM On Leakage<br>Current <sup>(6)</sup>               | I <sub>COM(ON)</sub>                            | V+ = 5.5V, V <sub>COM</sub> = +4.5V<br>V <sub>NO</sub> or V <sub>NC</sub> = +4.5V          | 25        | -1.0                | 0.20                | 1.0                 |       |
|  |   |  | Full      | 10                  |                     | 10                  |       |

### Electrical Specifications - Single +5V Supply (continued)

(V+ = +5V ± 10%, GND = 0V, V<sub>INH</sub> = 2.4V, V<sub>INL</sub> = 0.8V)

| Parameter                       | Symbol                | Conditions   | Temp(°C) | Min. <sup>(1)</sup> | Typ. <sup>(2)</sup> | Max. <sup>(1)</sup> | Units |
|---------------------------------|-----------------------|--|----------|---------------------|---------------------|---------------------|-------|
| Logic Input                     |                       |  |          |                     |                     |                     |       |
| Input High Voltage              | V <sub>IH</sub>       | Guaranteed logic High Level  | Full     | 2                   |                     |                     | V     |
| Input Low Voltage               | V <sub>IL</sub>       | Guaranteed logic Low Level   |          |                     |                     | 0.8                 |       |
| Input Current with Voltage High | I <sub>INH</sub>      | V <sub>IN</sub> = 2.4V, all others = 0.8V  |          | −1                  | 0.005               | 1                   | μA    |
| Input Current with Voltage Low  | I <sub>INL</sub>      | V <sub>IN</sub> = 0.8V, all others = 2.4V  |          | −1                  | 0.005               | 1                   |       |
| Dynamic                         |                       |  |          |                     |                     |                     |       |
| Turn-On Time                    | t <sub>ON</sub>       | V <sub>CC</sub> = 5V, Figure 1   | 25       |                     | 7                   | 15                  | ns    |
|                                 |                       |  | Full     |                     |                     | 20                  |       |
| Turn-Off Time                   | t <sub>OFF</sub>      |  | 25       |                     | 1                   | 7                   |       |
|                                 |                       |  | Full     |                     |                     | 10                  |       |
| Break-Before-Make               | t <sub>BBM</sub>      | Figure 3   | 25       |                     |                     | 10                  |       |
|                                 |                       |  | Full     | 5                   |                     |                     |       |
| Charge Injection <sup>(3)</sup> | Q                     | C <sub>L</sub> = 1nF, V <sub>GEN</sub> = 0V,<br>R <sub>GEN</sub> = 0 ohm, Figure 2 | 25       |                     | 1.5                 | 5                   | pC    |
| Off Isolation                   | OIRR                  | R <sub>L</sub> = 50 ohms, C <sub>L</sub> = 5pF,<br>f = 1MHz, Figure 4              |          |                     | 80                  |                     | dB    |
| Crosstalk <sup>(8)</sup>        | X <sub>TALK</sub>     | R <sub>L</sub> = 50 ohms, C <sub>L</sub> = 5pF,<br>f = 1MHz, Figure 5              |          |                     | 80                  |                     |       |
| NC or NO Capacitance            | C <sub>(OFF)</sub>    | f = 1MHz, Figure 6   |          |                     | 5.0                 |                     | pF    |
| COM Off Capacitance             | C <sub>COM(OFF)</sub> |  |          |                     | 5.0                 |                     |       |
| COM On Capacitance              | C <sub>COM(ON)</sub>  | f = 1MHz, Figure 7   |          |                     | 13                  |                     |       |
| −3dB Bandwidth                  | BW                    | R <sub>L</sub> = 50 ohms, Figure 8   | Full     |                     | 300                 |                     | MHz   |
| Supply                          |                       |  |          |                     |                     |                     |       |
| Power-Supply Range              | V+                    |  | Full     | 2                   |                     | 6                   | V     |
| Positive Supply Current         | I+                    | V <sub>CC</sub> = 5.5V, V <sub>IN</sub> = 0V or V+                                 |          |                     |                     | 1                   | μA    |

#### Notes:

- The algebraic convention, where most negative value is a minimum and most positive is a maximum, is used in this data sheet.
- Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
- Guaranteed by design.
- ΔR<sub>ON</sub> = R<sub>ON</sub> max. - R<sub>ON</sub> min.
- Flatness is defined as the difference between the maximum and minimum value of On-resistance measured.
- Leakage parameters are 100% tested at maximum rated hot temperature and guaranteed by correlation at +25°C.
- Off Isolation = 20log<sub>10</sub> [ V<sub>COM</sub> / (V<sub>NO</sub> or V<sub>NC</sub>) ]. See Figure 3.
- Between any two switches. See Figure 4.

### Electrical Specifications - Single +3.3V Supply

(V+ = +3.3V ± 10%, GND = 0V, V<sub>INH</sub> = 2.4V, V<sub>INL</sub> = 0.8V)

| Parameter  | Symbol                | Conditions  | Temp.(°C)  | Min. <sup>(1)</sup> | Typ. <sup>(2)</sup> | Max. <sup>(1)</sup> | Units |    |
|--|-----------------------|---|--|---------------------|---------------------|---------------------|-------|----|
| Analog Switch  |                       |   |  |                     |                     |                     |       |    |
| Analog Signal Range <sup>(3)</sup>                     | V <sub>ANALOG</sub>   |   |  | 0                   |                     | V+                  | V     |    |
| On-Resistance  | R <sub>ON</sub>       | V+ = 3V, I <sub>COM</sub> = −30mA,<br>V <sub>NO</sub> or V <sub>NC</sub> = 1.5V         | 25   |                     | 12                  | 14.0                | Ω     |    |
|  |                       |   | Full   |                     |                     | 17                  |       |    |
| On-Resistance Match<br>Between Channels <sup>(4)</sup> |                       | V+ = 3.3V, I <sub>COM</sub> = −30mA,<br>V <sub>NO</sub> or V <sub>NC</sub> = 0.8V, 2.5V | 25   |                     | 0.2                 | 0.5                 |       |    |
|  |                       |   | Full   |                     |                     | 1                   |       |    |
| On-Resistance<br>Flatness <sup>(3,5)</sup>             | R <sub>FLAT(ON)</sub> |   | 25   |                     | 0.5                 | 4                   |       |    |
|  |                       |   | Full   |                     |                     | 5                   |       |    |
| Dynamic  |                       |   |  |                     |                     |                     |       |    |
| Turn-On Time   | t <sub>ON</sub>       |   | V+ =3.3V, V <sub>NO</sub><br>or V <sub>NC</sub> = 1.5V, Figure 1 | 25                  |                     | 15                  | 25    | ns |
|  |                       | Full  |  |                     |                     | 40                  |       |    |
| Turn-Off Time  | t <sub>OFF</sub>      | 25  |  |                     | 1.5                 | 12                  |       |    |
|  |                       | Full  |  |                     |                     | 20                  |       |    |
| Break-Before-Make                                      | t <sub>BBM</sub>      | 25  |  |                     | 10                  |                     |       |    |
|  |                       | Full  |  | 5                   |                     |                     |       |    |
| Charge Injection <sup>(3)</sup>                        | Q                     | C <sub>L</sub> = 1nF, V <sub>GEN</sub> = 0V,<br>R <sub>GEN</sub> = 0V, Figure 2         | 25   |                     | 1.3                 | 5                   | pC    |    |
| Supply   |                       |   |  |                     |                     |                     |       |    |
| Positive Supply Current                                | I+                    | V+ = 3.6V, V <sub>IN</sub> = 0V or V+<br>All Channels on or off                         | Full   |                     |                     | 1                   | μA    |    |
| Logic Input  |                       |   |  |                     |                     |                     |       |    |
| Input High Voltage                                     | V <sub>IH</sub>       | Guaranteed logic high level   | Full   | 2                   |                     |                     | V     |    |
| Input Low Voltage                                      | V <sub>IL</sub>       | Guaranteed logic low level  | Full   |                     |                     | 0.8                 |       |    |
| Input High Current                                     | I <sub>INH</sub>      | V <sub>IN</sub> = 2.4V, all others = 0.8V   | Full   | −1                  |                     | 1                   | μA    |    |
| Input Low Current                                      | I <sub>INL</sub>      | V <sub>IN</sub> = 0.8V, all others = 2.4V   | Full   | −1                  |                     | 1                   |       |    |

#### Notes:

1. The algebraic convention, where most negative value is a minimum and most positive is a maximum, is used in this data sheet.
2. Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
3. Guaranteed by design.
4. ΔR<sub>ON</sub> = R<sub>ON</sub> max. - R<sub>ON</sub> min.
5. Flatness is defined as the difference between the maximum and minimum value of On-resistance measured.
6. Leakage parameters are 100% tested at maximum rated hot temperature and guaranteed by correlation at +25°C.
7. Off Isolation = 20log<sub>10</sub> [ V<sub>COM</sub> / (V<sub>NO</sub> or V<sub>NC</sub>) ]. See Figure 4.
8. Between any two switches. See Figure 5.

### Electrical Specifications - Single +2.5V Supply


(V+ = +2.5V ± 10%, GND = 0V, V<sub>INH</sub> = 2.4V, V<sub>INL</sub> = 0.8V)

| Parameter  | Symbol                | Conditions  | Temp.(°C) | Min. <sup>(1)</sup> | Typ. <sup>(2)</sup> | Max. <sup>(1)</sup> | Units |
|--|-----------------------|---|-----------|---------------------|---------------------|---------------------|-------|
| Analog Switch  |                       |   |           |                     |                     |                     |       |
| Analog Signal Range <sup>(3)</sup>                     | V <sub>ANALOG</sub>   |   |           | 0                   |                     | V+                  | V     |
| On-Resistance  | R <sub>ON</sub>       | V+ = 2.5V, I <sub>COM</sub> = −30mA,<br>V <sub>NO</sub> or V <sub>NC</sub> = 1.5V       | 25        |                     | 20                  | 22                  | Ω     |
|  |                       |   | Full      |                     |                     | 26                  |       |
| On-Resistance Match<br>Between Channels <sup>(4)</sup> | ΔR <sub>ON</sub>      | V+ = 2.5V, I <sub>COM</sub> = −30mA,<br>V <sub>NO</sub> or V <sub>NC</sub> = 0.8V, 2.5V | 25        |                     | 0.3                 | 0.5                 |       |
|  |                       |   | Full      |                     | 1                   |                     |       |
| On-Resistance<br>Flatness <sup>(3,5)</sup>             | R <sub>FLAT(ON)</sub> |   | 25        |                     | 0.5                 | 5                   |       |
|  |                       |   | Full      |                     |                     | 6                   |       |
| Dynamic  |                       |   |           |                     |                     |                     |       |
| Turn-On Time   | t <sub>ON</sub>       | V+ = 2.5V, V <sub>NO</sub><br>or V <sub>NC</sub> = 1.5V, Figure 1                       | 25        |                     | 20                  | 30                  | ns    |
|  |                       |   | Full      |                     | —                   | 45                  |       |
| Turn-Off Time  | t <sub>OFF</sub>      |   | 25        |                     |                     | 20                  |       |
|  |                       |   | Full      |                     | —                   | 30                  |       |
| Break-Before-Make                                      | t <sub>BBM</sub>      |   | 25        |                     | 10                  |                     |       |
|  |                       |   | Full      | 5                   |                     |                     |       |
| Charge Injection <sup>(3)</sup>                        | Q                     | C <sub>L</sub> = 1nF, V <sub>GEN</sub> = 0V,<br>R <sub>GEN</sub> = 0V, Figure 2         | 25        |                     | 0.9                 | 5                   | pC    |
| Supply   |                       |   |           |                     |                     |                     |       |
| Positive Supply Current                                | I+                    | V+ = 2.5V, V <sub>IN</sub> = 0V or V+<br>All Channels on or off                         | Full      |                     |                     | 1                   | μA    |
| Logic Input  |                       |   |           |                     |                     |                     |       |
| Input High Voltage                                     | V <sub>IH</sub>       | Guaranteed logic high level   | Full      | 2                   |                     |                     | V     |
| Input Low Voltage                                      | V <sub>IL</sub>       | Guaranteed logic low level  | Full      |                     |                     | 0.8                 |       |
| Input High Current                                     | I <sub>INH</sub>      | V <sub>IN</sub> = 2.4V, all others = 0.8V   | Full      | −1                  |                     | 1                   | μA    |
| Input Low Current                                      | I <sub>INL</sub>      | V <sub>IN</sub> = 0.8V, all others = 2.4V   | Full      | −1                  |                     | 1                   |       |


#### Notes:

1. The algebraic convention, where most negative value is a minimum and most positive is a maximum, is used in this data sheet.
2. Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
3. Guaranteed by design.
4. ΔR<sub>ON</sub> = R<sub>ON</sub> max. - R<sub>ON</sub> min.
5. Flatness is defined as the difference between the maximum and minimum value of On-resistance measured.
6. Leakage parameters are 100% tested at maximum rated hot temperature and guaranteed by correlation at +25°C.
7. Off Isolation = 20log<sub>10</sub> [ V<sub>COM</sub> / (V<sub>NO</sub> or V<sub>NC</sub>) ]. See Figure 4.
8. Between any two switches. See Figure 5.


## Test Circuits/Timing Diagrams



**Figure 1. Switching Time**




**Figure 2. Charge Injection**




**Figure 3. Break-Before-Make Interval**


**Test Circuits/Timing Diagrams (continued)**




**Figure 4. Off Isolation/On-Channel Bandwidth**




**Figure 5. Crosstalk**



**Figure 6. Channel-Off Capacitance**




**Figure 7. Channel-On Capacitance**



**Figure 8. Bandwidth**

### 6-Pin SC70 (C) Package



### Ordering Information

| Part Number | Package | Package Top Mark |
|-------------|---------|------------------|
| PI5A4599ACX | SC70-6  | A63              |